

“VELIKO MONOGRADE” engine oils are available in SAE 30, SAE 40, SAE 50 grades. These are super quality heavy duty diesel engine crankcase lubricating oil blended from selected highly refined base stock with a finely balanced additive package including detergent, dispersant, antioxidant, anti-wear, anticorrosion and antifoam agents.

FEATURES

- These oil have exceptional thermal and oxidation stability to arrest decomposition in engines operating at high ring zone temperatures.
- They have a good built in alkaline reserve to combat corrosive wear that may result from the use of high Sulphur fuel.

BENEFITS

- Excellent oxidation stability and added protection against engine deposits, rust, corrosion and wear.
- Quicker engine start and longer engine life.
- Longer service life-fewer oil drains.
- High degree of engine cleanliness.

CHARACTERISTICS

- Outstanding protection against corrosion
- Good Anti-wear Property
- High Oxidation stability
- Excellent Anti-Rust Property

APPLICATIONS

Recommended for use in turbocharged diesel engine, naturally aspirant diesel & certain high powered petrol engines. In naturally aspirated diesel engines these grades give a very long drain period.

PERFORMANCE SPECIFICATION

These graded meet API CD/SD, U.S. Military MIL-L-2104C performance levels and HD type 5 of IS:10356-1982 specifications.

TESTING SPECIFICATION

ISO Vis Grade	SAE 30	SAE 40	SAE 50
Viscosity at 100 °C	11.7 cST	15.9 cST	19 cST
Viscosity Index	97	93	92
Flash Point °C	220	225	230
Pour Point °C	-6	-6	-6
TBN, mg/KOH/gm	13	13	13