

“VELIKO MULTIGRADE” engine oil is formulated from highly refined based stocks and selected additive packages to give very high viscosity index, high detergency level and excellent oxidation stability.

FEATURES

- Its outstanding viscosity related performance meets round year requirements.
- These oil have excellent thermal and oxidation stability to arrest decomposition in engines operating at high ring zone temperatures.

BENEFITS

- Excellent thermal and oxidation stability.
- Outstanding viscosity related function to meet round the year requirements
- Long drain period
- Anti wear property to extend life of engine

CHARACTERISTICS

- Good Anti-wear Property
- High Oxidation stability
- Excellent Anti-Rust Property
- Outstanding thermal stability

APPLICATIONS

Recommended for all type if diesel engines, gen-set engines, hydro pump set engines. 15w-40 grades are also recommended for use by some of the generating sets operating on HSD or LDO or LSHS as fuel

PERFORMANCE SPECIFICATION

These graded meet API CD/SD, U.S. Military MIL-L-2104C performance levels and HD type 5 of IS:-496-1982 & IS:10356-1982 specifications.

TESTING SPECIFICATION

ISO Vis Grade	20W/40	20W/50	15W/40
Viscosity at 100 °C	14.9 cST	19 cST	16 cST
Viscosity Index	120	120	120
Flash Point °C	200	200	200
Pour Point °C	-21	-21	-22